



















推奨スポーク長一覧 作成:2026.7.30 (株) グロータック

対象ハブ：EQUAL DISC ハブ									計算値				偶数長さでの推奨			
		Type	GROWTAC Model No	ERD (mm)	Offset (mm)	Height (mm)	Spoke holes	組み方	後左 Spoke (mm)	後右 Spoke (mm)	前左 Spoke (mm)	前右 Spoke (mm)	後左 Spoke (mm)	後右 Spoke (mm)	前左 Spoke (mm)	前右 Spoke (mm)
1		700C Tubeless ready Offset holes 370g±15g	RMCD-292230-A	579	2.5	30	24	2クロス	279.6	278.4	280.2	279.9	280	278	280	280
2		700C Tubeless ready Offset holes 400g±15g	RMCD-292240-A	559	2.5	40	24	2クロス	269.6	268.4	270.3	269.9	270	268	270	270
3		700C Tubeless ready Offset holes 440g±15g	RMCD-292250-A	539	2.5	50	24	2クロス	259.7	258.5	260.3	260.0	260	258	260	260
4		700C Tubeless ready 370g±15g	RMCD-292230-G	579	0	30	24	2クロス	279.6	278.4	280.2	279.9	280	278	280	280
5		700C Tubeless ready 400g±15g	RMCD-292240-G	559	0	40	24	2クロス	269.6	268.4	270.3	269.9	270	268	270	270
6		700C Tubeless ready 440g±15g	RMCD-292250-G	539	0	50	24	2クロス	259.7	258.5	260.3	260.0	260	258	260	260
7		700C Tubeless ready 480g±15g	RMCD-282160-G	520	0	60	24	2クロス	249.6	247.8	249.6	249.9	250	248	250	250
8		27 inch Tubular 290g±15g	RMCD-280030-B	579	0	30	24	2クロス	279.9	278.2	280.0	280.2	280	278	280	280
9		650B Tubeless ready Offset holes 360g±15g	RMCD-302430-C	540	2.8	30	24	2クロス	260.2	259.0	260.8	260.5	260	258	260	260
10		27 inch Tubular 290g±15g	RMCD-250030-B	580	0	30	24	2クロス	280.4	278.7	280.5	280.7	280	278	280	280
11		27 inch Tubular 335g±15g	RMCD-250040-B	559	0	40	24	2クロス	269.9	268.2	270	270.3	270	268	270	270
12		27 inch Tubular 360g±15g	RMCD-250050-B	540	0	50	24	2クロス	260.5	258.7	260.5	260.8	260	258	260	260
13		700C Hookless Tubeless ready Offset holes	RMCD-302530-E	579	2.8	30	24	2クロス	279.6	278.4	280.3	279.8	280	278	280	280
14		700C Tubeless ready	RMCD-383239-G	561	0	39	24	2クロス	269.9	268.2	269.9	270.2	270	268	270	270
15		700C Tubeless ready Offset holes	RMCD-292230-D	579	2.5	30	28	3クロス	285.7	284.8	285.6	286.0	286	284	286	286
16		700C Tubeless ready Offset holes	RMCD-292240-D	559	2.5	40	28	3クロス	275.8	274.9	275.7	276.1	276	274	276	276
17		700C Tubeless ready Offset holes	RMCD-292250-D	539	2.5	50	28	3クロス	265.9	265.0	265.8	266.2	266	264	266	266
18		700C Tubeless ready	RMCD-292230-H	579	2.5	30	28	3クロス	285.7	284.8	285.6	286.0	286	284	286	286
19		700C Tubeless ready	RMCD-292240-H	559	2.5	40	28	3クロス	275.8	274.9	275.7	276.1	276	274	276	276
20		700C Tubeless ready	RMCD-292250-H	539	2.5	50	28	3クロス	265.9	265.0	265.8	266.2	266	264	266	266
21		700C Hookless Tubeless ready Offset holes	RMCD-302530-F	579	2.8	30	28	3クロス	285.7	284.9	285.7	286.0	286	284	286	286
22		700C Tubeless ready	RMCD-383239-H	561	0	39	28	3クロス	276.8	275.4	276.2	277.1	277	275	277	277

